

SAMPLE	NAME/SKU	QTY	CUT
	Simply Blooming 2456-36 <i>Aqua/Purple</i>	3/4 YD	(4) 6-1/2" squares for center (4) 4-1/2" x WOF for outside borders.
	Mini Tile 2459-60 <i>Chocolate/Purple</i>	1/3 YD	(16) 3-1/2" x 6-1/2" rectangles for flying geese bases.
	Papyrus 2458-36 <i>Aqua/Purple</i>	1/2 YD	(12) 3-1/2" x 12-1/2" for inner sashings.
	Mini Tile 2459-84 <i>Teal</i>	1/3 YD	(25) 3-1/2" squares.
	Vine 2460-81 <i>Light Teal</i>	1/8 YD	(8) 3-7/8" squares cut in half diagonally to yield 16 half square triangles.
	Vine 2460-70 <i>Gravel</i>	1/3 YD	(32) 3-1/2" squares.
	Geometric 2461-36 <i>Light Amethyst</i>	1 YD INCLUDES BINDING	(8) 3-7/8" squares cut in half diagonally to yield 16 half square triangles. (4) 4-1/2" squares. (4) 1-1/2" x WOF strips.

WOF= WIDTH OF FABRIC

Extra yardage has been added for fussy cutting centers and lining up stripes. This wall hanging is made of (4) 12" blocks, inner sashing with cornerstones, spacer strip and borders. 1/4" seam allowances have been included in cutting instructions. Read through instructions before beginning. Refer to diagrams and color photo for placement.

BLOCK ASSEMBLY Follow diagram as follows.

1. Take (1) 3-1/2" **D** square and either fold diagonally and press with iron or draw a diagonal line on wrong side. Place one **D** square on upper left hand corner of square **A**, right sides together. Sew on diagonal line.

2. Flip the lower right hand corner square up to upper left hand corner. Press. Trim excess fabric on reverse side to 1/4" as shown on right. Repeat steps for the remaining (3) squares to complete center block. Make 4 blocks. Set aside.

3. Next assemble the Flying Geese units, following diagram below.


- Take (2) 3 1/2" squares of **F**. Then either draw a diagonal line across the square or fold diagonally and press with iron.
- Place one square on left hand side of a 3 1/2" x 6 1/2" **B** rectangle, right sides together. Sew on diagonal line.
- Flip the lower right hand corner of square up to upper left hand corner. Press. Trim excess fabric on reverse side to 1/4" as shown below. Repeat for right hand corner. Make 16 units.



3. Take (1) **E** and (1) **G** half square triangle and sew together diagonally, repeat to make 15 more squares.

4. Add (2) **E-G** squares to ends of **B-F** unit. Make 8. Next add (2) **B-F** units to sides of **CENTER BLOCK**. Make 4. Then add **B-E-F-G** units to top and bottom of **CENTER BLOCK**. Make 4 blocks. Follow diagram on the left.

5. For sashing follow diagrams below. First complete Row 1 and Row 2 by adding **C** strips to sides of block. Add 2-1/2" **D** squares to the remaining **C** strips. Then add **D-C** strips to top, middle and bottom to complete quilt center.



6. Next add 1-1/2" **G** inner border strips to sides of quilt top, trim to fit. Repeat for top and bottom.

6. Next add 1-1/2" **G** inner border strips to sides of quilt top, trim to fit. Repeat for top and bottom.

7. **OUTER BORDER:** Measure width of quilt top (should be about 34"). Cut (4) 4-1/2" x 34" **A** strips. Sew 1 strip to each side of quilt top. To remaining **A** strips add **G** 4-1/2" squares to ends. Sew **AG** strips to top and bottom of quilt top.

FINISHING Cut batting and backing 3" larger than top on all sides. Assemble the quilt sandwich by placing the backing, batting and top together in layers and baste or pin with safety pins. Machine quilt as desired. When quilting is completed, trim excess batting and backing. Bind in the usual manner.

FINISHED SIZE: 43" SQUARE.